



DECK

Built to be tough and reliable. Aluminum and Steel construction. 17,000 lb. structural capacity.

BODY

Low profile and versatile. Various grid options available. 3,500 lb. or 5,000 lb. lift capacities.

WINCH

Up to 12,000 lb. capacity winches for maximum pulling power.

SPECIFICATIONS

A MULTIPURPOSE WORKHORSE THAT WON'T LET YOU DOWN

The 8.5 Ton XLP Carrier is available in steel or aluminum, with multiple deck length and width configurations and a 17,000-lb. structural deck capacity for more strength and durability on the job.

BECAUSE THE WORK DEMANDS IT.

Want a truck that works as hard as you do?

Visit our website at Jerrdan.com to find your nearest distributor.

CARRIER DECK	
Capacity	17,000 lbs.
Deck Width	96 in., 102 in.
Deck Length	22 ft., 24 ft., 26 ft., 28 ft., 30 ft.
Material Type	Steel or Aluminum
WHEEL LIFT	
3,500 LB WHEEL LIFT	
Lift Capacity	3,500 lbs.
Tow Capacity	10,000 lbs.
Maximum Extended Reach from Tail to Bed	65 in.
5,000 LB. WHEEL LIFT	
Lift Capacity	5,000 lbs.
Tow Capacity	12,000 lbs.
Maximum Extended Reach from Tail to Bed	67 in.
WINCH	
Winch Capacity	Single 10,000 lbs. or 12,000 lbs. Dual 8,000 lbs.
CHASSIS	
Minimum GVWR (W/o wheel lift)	25,500 lbs.
Minimum GVWR (W/ wheel lift)	33,000 lbs.
Cab to Axle (CA) Range	138 in.-150 in. (22 ft. deck) 156 in.-168 in. (24 ft. deck) 180 in.-192 in. (26 ft. deck) 204 in.-214 in. (28 ft. deck) 228 in.-238 in. (30 ft. deck)

MEDIUM DUTY CARRIER

8.5 TON XLP

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 functions)		•
DECK & SUBFRAME		
STEEL		
Single Sheet 3/16 in. Diamond or Smooth Decking	•	
5 in. Removable Tubular Steel Rails		•
5 in. Polished Aluminum Blade Rails		•
ALUMINUM		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5 in. Fixed Blade Rails (NGAF)		•
STEEL & ALUMINUM		
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Headboard - Deck Mounted or Stationary Frame Mounted	•	
Side Recovery System (SRS)		•
Galvanized Subframe & Wheel Lift		•
102 in. Deck Width		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Wheel Lift Grids (Manual)		•
Camlocks ILO of T-Handle (Manual Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available)		•
*Option available when wheel lift is deleted		
ACCESSORIES		
Toolbox (36 in., 48 in. or 60 in.)		•
Toolbox Trays		•
WINCH & WIRE ROPE		
10,000 lb. Worm Gear Winch w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope		•
12,000 lb. Worm Gear w/ 7/16 in. x 56 ft. EIPS Galvanized Wire Rope (Only available w/ single manual free spool)		•
10,000 lb. Sliding Planetary Winch w/ 7/16 in x 56 ft. EIPS Galvanized Wire Rope		•
Dual 8,000 lb. Worm Gear Winches w/ 3/8 in. x 56 ft. EIPS Galvanized Wire Rope (Only available on 28 ft. & 30 ft.)		•
Dual Side Manual Free Spool (10,000 lb. Winch only)		•
Air Controlled Winch Free Spool (10,000 lb. Winch only)		•