

WORK READY TRUCKS

Oilfield and Equipment Ready

**2021 PETERBILT 367
TULSA WINCH RN65 PACKAGE**

VEHICLE SPECIFICATIONS

- Model 367 conventional
- XP15 Engine, 565 HP at 1950 RPM
- 58" sleeper
- FGAWR 20,000 lbs
- RGAWR 46,000 lbs

EQUIPMENT SPECIFICATIONS

- Tulsa Roughneck 65 - 65,000lb line pull at up to 52 FPM with a 1" cable
- Steel cab guard with stainless steel mirror detail package and integrated top mounted light bar assembly
- 3" steel Unibody subframe throughout
- Steel winch deck structure for strength with aluminum vented decking walking surface
- 3/16" aluminum fenders with center support to eliminate sagging
- Custom fabricated hydraulic in frame tank with remote mount dual return filters
- PTO, vane pump and directional control valve with manual and cab control
- Steel structure "Dimensional" sign with mirror stainless detail back able to be air controlled from in cab
- Two frame mounted aluminum tool boxes with walk up steps for deck access
- 4 locking chain hangers mounted against cab guard for deck chains and boomers
- Steel frame mounted pull out chain hangers for steer and drive chains
- One piece tow apron with 7" by 34" greaseable live roll, integrated ramps and lighting
- Holland 3500 series fifth wheel and slider
- Insert tray in front of fifth wheel to house all air and electrical components
- Two deck pin tray holders with cargo securement
- Complete in cab control for all winch and lighting options
- Pull out adjustable LED lighting facing rear work area and mounted at deck height
- LED work lights mounted on top of cab guard
- Complete CMVSS compliant LED light package
- NSM Applied

For internal use and reference only!