

WORK READY TRUCKS

High Pressure Fluid Pumping

2020 KENWORTH T370 6 CUBE STAINLESS STEEL TC406 PRESSURE TRUCK

VEHICLE SPECIFICATIONS

- Single axle 4x2, conventional cab
- Paccar PX-9 engine - 330 HP at 2000 RPM
- Allison 3500 RDS
- 14,600 lbs FGAWR
- 23,000 lbs RGAWR

EQUIPMENT SPECIFICATIONS

- Lazer 6 Cube Stainless Steel 2 compartment TC406 Tank
- Comes with rear TC spec bumper, valves, 2" T&E pump, 3" sumps and 2" venting
- PRATISSOLI MKS40A, 182 LPM 5800 PSI pressure pump
- HANNAY Hose reel for 100 feet of 1" hose (hydraulic operation) with remote control
- TITAN TD80 fluid gauge with digital readout
- Flowmeter with digital readout (turbine included)
- All low pressure plumbing from tank to pumps in stainless steel
- High pressure "Tree" from PRATISSOLI to reel including separate bleed backs to each compartment
- Pressure gauge on both low and high-pressure plumbing
- BAIRD pressure relief valve plumbed into high side
- Closed Loop Piston Hydraulic system for pressure pump with separate speed and pressure control, tandem pump to run T&E
- Hose reel and Hydraulic cooler
- Deck mounted fire extinguisher
- Custom Fabricated Stainless hydraulic tank with in tank return filter and sight gauge for volume and temperature
- Kick back safety valves installed on high side plumbing
- Steel blasted and powder coated
- Steel deck structure to house all components
- All Hoses and fittings required
- Positive air shutdown
- Tank walking deck and rail with ladder
- Complete operators/ parts manual

For internal use and reference only!