

WIDE-OUT™ XL

Heavy-Duty Commercial, High-Efficiency Plow that gives operators full control over wing activation



WIDE-OUT™

High-Efficiency Plow for contractors that provides full control over wing activation



FEATURES	DESCRIPTION	FEATURES	DESCRIPTION
BLADE SIZES	8'6" extends to 11' in straight and 9'10" in scoop	BLADE SIZES	8' extends to 10' in straight and 8'10" in scoop
BLADE CONSTRUCTION	14-gauge powder coated steel.	BLADE CONSTRUCTION	14-gauge powder coated steel.
HYDRAULIC WING EXTENSIONS	Independently position each wing to maximize blade width and move more snow.	HYDRAULIC WING EXTENSIONS	Independently position each wing to maximize blade width and move more snow.
FLARED WINGS	Flared wing extensions as tall as 36" maximize efficiency and aggressively cast snow further when windrowing.	FLARED WINGS	Flared wing extensions as tall as 36" maximize efficiency and aggressively cast snow further when windrowing.
HEAVY-DUTY SLIDE BOX	Reduce the amount of snow that rolls off the top of the plow with standard flared wings that rise 6"-10" from the center pin.	HEAVY-DUTY SLIDE BOX	Reduce the amount of snow that rolls off the top of the plow with standard flared wings that rise 6"-10" from the center pin.
STRUCTURAL REINFORCEMENT	Eight vertical ribs, a heavy-duty quadrant and a dual WESTERN® POWER BAR provide exceptional torsional strength and rigidity across the entire back of the plow blade, eliminating blade twisting.	STRUCTURAL REINFORCEMENT	Six vertical ribs, a heavy-duty quadrant and a dual WESTERN POWER BAR provide exceptional torsional strength and rigidity across the entire back of the plow blade, eliminating blade twisting.
LIFT RAM	1 3/4"-diameter lift ram for more lifting power.	LIFT RAM	1 3/4"-diameter lift ram for more lifting power.
ACCESSORIES	Back Drag Edge, Rubber Deflector, Shoe Kits, Poly Moldboard Cutting Edge, Poly Wing Cutting Edge, 5/8" Steel Cutting Edge, Shock Absorber	ACCESSORIES	Back Drag Edge, Rubber Deflector, Shoe Kits, Poly Moldboard Cutting Edge, Poly Wing Cutting Edge, 5/8" Steel Cutting Edge, Shock Absorber
TRUCK CLASS	3, 4, 5	TRUCK CLASS	2, 3, 4

THE WESTERN WIDE-OUT AND WIDE-OUT XL ARE FOUR PLOWS IN ONE.



Retracted Straight

Expanded Straight

Windrow Left / Right Position

Scoop Mode



WIDE-OUT™**



WIDE-OUT™ XL



PRODIGY™

PLOW TYPE	WINGED	WINGED	WINGED
MOLDBOARD OPTIONS	Steel	Steel	Steel
BLADE WIDTH	Retracted: 8' (2.44 m) Expanded: 10' (3.05 m) Scoop: 8'10" (2.69 m)	Retracted: 8'6" (2.59 m) Expanded: 11' (3.35 m) Scoop: 9'10" (3.00 m)	Scoop: 8'7" (2.62 m) Wings Pinned: 9'8" (2.95 m)
BLADE HEIGHT	At Center: 31" (78.74 cm) At End: 35" (88.90 cm)	At Center: 31" (78.74 cm) At End: 36" (91.44 cm)	29.5" (74.93 cm)
BLADE THICKNESS	14 ga	14 ga	12 ga
SHOCK ABSORBERS	Optional	Optional	Optional
TRIP SPRINGS	4	4	4
RIBS	6	8	8
LIFT CYLINDER	1.75" x 8" (4.45 cm x 20.32 cm)	1.75" x 8" (4.45 cm x 20.32 cm)	1.5" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	1.5" x 10" (3.81 cm x 25.40 cm)	1.5" x 10" (3.81 cm x 25.40 cm)	1.5" x 10" (3.81 cm x 25.40 cm)
PLOWING WIDTH (FULL ANGLE)	Retracted: 7'2" (2.18 m) Expanded: 9' (2.74 m) Scoop: 7'11" (2.41 m)	Retracted: 7'11" (2.41 m) Expanded: 10'6" (3.20 m) Scoop: 9'6" (2.90 m)	Full Angle: 7'10" (2.39 m) Scoop: 8'7" (2.61 m)
APPROX. WEIGHT* (LESS MOUNT)	1,057 lbs (479 kg)	1,120 lbs (507 kg)	911 lbs (413 kg)
CUTTING EDGE	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount® 2	UltraMount 2	UltraMount 2

* UltraMount 2 mount weight range: 28 lb to 145 lb (12.70 kg to 65.77 kg)

**All product features and specifications listed in this brochure apply to WIDE-OUT snowplows with serial numbers beginning with 180210 and higher



PRO PLUS® HD

PRO PLUS®

PLOW TYPE	STRAIGHT	STRAIGHT	STRAIGHT	STRAIGHT
MOLDBOARD OPTIONS	Steel	Steel	Steel	Steel
BLADE WIDTH	10' (3.05 m)	8' (2.44 m)	8'6" (2.59 m)	9' (2.74 m)
BLADE HEIGHT	34" (86.36 cm)	31.5" (80.01 cm)	31.5" (80.01 cm)	31.5" (80.01 cm)
BLADE THICKNESS	11 ga	12 ga	12 ga	12 ga
SHOCK ABSORBERS	2	2	2	2
TRIP SPRINGS	6	4	4	4
RIBS	8	8	8	8
LIFT CYLINDER	1.75" x 8" (4.45 cm x 20.32 cm)	1.5" x 8" (3.81 cm x 20.32 cm)	1.5" x 8" (3.81 cm x 20.32 cm)	1.5" x 8" (3.81 cm x 20.32 cm)
ANGLING RAMS	2" x 12.5" (5.08 cm x 31.75 cm)	1.5" x 12" (3.81 cm x 30.48 cm)	1.5" x 12" (3.81 cm x 30.48 cm)	1.5" x 12" (3.81 cm x 30.48 cm)
PLOWING WIDTH (FULL ANGLE)	8'9" (2.67 m)	6'11" (2.11 m)	7'4" (2.24 m)	7'9" (2.36 m)
APPROX. WEIGHT* (LESS MOUNT)	1,076 lbs (487 kg)	823 lbs (373 kg)	840 lbs (381 kg)	858 lbs (389 kg)
CUTTING EDGE	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)	½" x 6" (1.27 cm x 15.24 cm)
MOUNT TYPE	UltraMount 2	UltraMount 2	UltraMount 2	UltraMount 2

* UltraMount 2 mount weight range: 28 lb to 145 lb (12.70 kg to 65.77 kg)